








































IP ÜRÜNLER			
ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
2MP IP KAMERA			
DS-2CD1021G2-LIUF (Dahili mikrofon)		2 MP Smart Hybrid Light Bullet Network Kamera 1/2.9" Progressive Scan CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 20m, DC12V & PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included. Motion Detection 2.0	91
DS-2CD1121G2-LIUF (Dahili mikrofon)		2 MP Smart Hybrid Light Dome Network Kamera 1/2.9" Progressive Scan CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 20m, DC12V & PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included. Motion Detection 2.0	91
DS-2CD1023G2-LIUF (Dahili mikrofon)		2 MP Smart Hybrid Light Bullet Network Kamera High quality imaging with 2 MP resolution;Support Human and Vehicle Detection;Smart Hybrid Light: advanced technology with long range;Built-in microphone for real-time audio security;Efficient H.265+ compression technology;Support on-board storage up to 512 GB(SD card slot);Water and dust resistant (IP67);Motion Detection 2.0	102
DS-2CD1323G2-LIUF (Dahili mikrofon)		2 MP Smart Hybrid Light Turet Network Kamera High quality imaging with 2 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);	102
DS-2CD1T23G2-LIUF/SL (Dahili mikrofon)		2 MP Smart Hybrid Light Bullet Network Kamera Live Guard 1/3" Progressive CMOS, ICR,1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone & speaker, audio & strobe light alarm, DC12V & PoE, Support mobile monitoring via Hik-Connect; Support on-board storage up to 512 GB (SD card slot) - Motion Detection 2.0	124
DS-2CD1027G2H-LIUF (Dahili mikrofon)		2 MP ColorVu & Smart Hybrid Light Bullet Network Kamera High quality imaging with 2 MP resolution; Support Human and Vehicle Detection Motion Detection 2.0; Smart Hybrid Light: advanced technology with long range; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot); Built-in microphone for real-time audio security; Water and dust resistant (IP67); Motion Detection 2.0	131
			
DS-2CD1327G2H-LIUF (Dahili mikrofon)		2 MP ColorVu & Smart Hybrid Light Dome Network Kamera High quality imaging with 2 MP resolution; Support Human and Vehicle Detection Motion Detection 2.0; Smart Hybrid Light: advanced technology with long range; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot); Built-in microphone for real-time audio security; Water and dust resistant (IP67); Motion Detection 2.0	131
			








ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<p>YENİ</p> <p>DS-2CD1T27G2H-LIUF/SL (Dahili mikrofon)</p> <p>ColorVu</p>		<p>2 MP ColorVu & Smart Hybrid Light Bullet Network Kamera Live Guard</p> <p>1/3" Progressive CMOS, ICR, 1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect;</p> <p>*-F: SD Card Slot (up to 512GB) *power supply is not included; Motion Detection 2.0</p>	157
<p>YENİ</p> <p>DS-2CD1027G3-LIUF</p> <p>ColorVu 3.0</p>		<p>2 MP ColorVu 3.0 Fixed Bullet Network Kamera</p> <p>1/2.8" Progressive CMOS, ICR, 1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+/H.264, WDR, 3D DNR, BLC, HLC, Smart hybrid light, IR or white light range: up to 30m, DC12V & PoE power supply, Support remote mobile management via Hik-Connect</p> <p>* Motion Detection 3.0, more accurate on person and vehicle classification; *-F: SD Card Slot (up to 512GB)</p>	146
<p>YENİ</p> <p>DS-2CD1327G3-LIUF</p> <p>ColorVu 3.0</p>		<p>2 MP ColorVu 3.0 Fixed Dome Network Kamera</p> <p>1/2.8" Progressive CMOS, ICR, 1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+/H.264, WDR, 3D DNR, BLC, HLC, Smart hybrid light, IR or white light range: up to 30m, DC12V & PoE power supply, Support remote mobile management via Hik-Connect</p> <p>* Motion Detection 3.0, more accurate on person and vehicle classification; *-F: SD Card Slot (up to 512GB)</p>	146
<p>YENİ</p> <p>DS-2CD1027G3-LIUF/SL</p> <p>ColorVu 3.0</p>		<p>2 MP ColorVu 3.0 Fixed Bullet Network Kamera, Live Guard</p> <p>1/2.8" Progressive CMOS, ICR, 1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+/H.264, WDR, 3D DNR, BLC, HLC, Smart hybrid light, IR or white light range: up to 30m, DC12V & PoE power supply, Support remote mobile management via Hik-Connect</p> <p>* Motion Detection 3.0, more accurate on person and vehicle classification; *-F: SD Card Slot (up to 512GB)</p>	157
<p>DS-2CD1623G2-LIZSU (Dahili mikrofon)</p>		<p>2MP Motorize Varifokal Lensli IR Bullet Kamera Smart Hybrid Light & Motion Detection 2.0</p> <p>1/3" Progressive CMOS, ICR, 1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect *-S: alarm and audio</p> <p>*power supply is not included</p>	223
<p>DS-2CD1723G2-LIZSU (Dahili mikrofon)</p>		<p>2MP Motorize Varifokal Lensli IR Dome Kamera Smart Hybrid Light & Motion Detection 2.0</p> <p>1/3" Progressive CMOS, ICR, 1920 × 1080: 25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect; *-S: alarm and audio</p> <p>*power supply is not included</p>	223
<p>DS-2CD2523G2-LIS2U (Dahili mikrofon)</p>		<p>2MP IR Mini Dome Acusense Kamera Acusense & Smart Hybrid Light & 120dB WDR</p> <p>1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-S model: Audio/Alarm IO</p> <p>* -2U: Built-in Dual-Array Microphone</p>	262








ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-2CD2T23G2-LIS2U/SL		2MP Bullet Acusense Kamera & Live Guard & Acusense & Smart Hybrid Light & 120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; Hik-Connect cloud service *-2LI/4LI model: 3000K Warm LED; EXIR, up to 60m/80m * -2U:Built-in Dual-Array Microphone;	255
4MP IP KAMERA			
YENİ			
DS-2CD1041G2-LIUF (Dahili mikrofon)		4 MP Smart Hybrid Light Fixed Bullet Network Kamera 1/2.8" Progressive Scan CMOS, ICR, 2560 × 1440:25fps(P)/30fps(N), H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 20m, DC12V & PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included;Motion Detection 2.0	124
YENİ			
DS-2CD1141G2-LIUF (Dahili mikrofon)		4 MP Smart Hybrid Light Fixed Dome Network Kamera 1/2.8" Progressive Scan CMOS, ICR, 2560 × 1440:25fps(P)/30fps(N), H.265+/H.264+&H.264, 3D DNR, BLC, IR range: up to 20m, DC12V & PoE,Support mobile monitoring via Hik-Connect , TF card slot, *power supply no included;Motion Detection 2.0	124
DS-2CD1043G2-LIUF (Dahili mikrofon)		4MP Smart Hybrid Light Bullet Network Kamera High quality imaging with 4 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);Motion Detection 2.0	153
DS-2CD1343G2-LIUF (Dahili mikrofon)		4MP Smart Hybrid Light Turret Network Kamera High quality imaging with 4 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Built-in microphone for real-time audio security; Efficient H.265+ compression technology; Support on-board storage up to 512 GB (SD card slot) (Optional); Water and dust resistant (IP67);Motion Detection 2.0	153
YENİ			
DS-2CD1T43G2-LIUF/SL (Dahili mikrofon)		4MP Smart Hybrid Light Bulltet Network Kamera Live guard 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), 2304x1296:25fps(P)/30fps(N), H.265+/H.265/H.264+&H.264, 3D DNR, BLC, Smart Hybrid Light with IR and white light, range: up to 50m, DC12V & PoE, Motion 2.0 human and vehicle classification, Support mobile monitoring via Hik-Connect; *-F: Built-in Microphone, TF card slot;Motion Detection 2.0	183
DS-2CD1043G2-LIUF/SL		4MP Smart Hybrid Light Bulltet Network Kamera Live guard 1/3" Progressive CMOS, ICR,2560 × 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone & speaker, audio & strobe light alarm, DC12V & PoE, Support mobile monitoring via Hik-Connect; *-F: Built-in Microphone, TF card slot;Motion Detection 2.0	164
DS-2CD1343G2-LIUF/SL		4MP Smart Hybrid Light Dome Network Kamera Live guard 1/3" Progressive CMOS, ICR,2560 × 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone & speaker, audio & strobe light alarm, DC12V & PoE, Support mobile monitoring via Hik-Connect; *-F: Built-in Microphone, TF card slot;Motion Detection 2.0	164



ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-2CD1047G2H-LIUF (Dahili mikrofon) ColorVu		4MP ColorVu & Smart Hybrid Light Bullet Network Kamera 1/3" Progressive CMOS, ICR,2560 × 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; *-F: SD Card Slot (up to 512GB) *power supply is not included;Motion Detection 2.0	197
DS-2CD1347G2H-LIUF (Dahili mikrofon) ColorVu		4MP ColorVu & Smart Hybrid Light Turret Network Kamera 1/3" Progressive CMOS, ICR,2560 × 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; *-F: SD Card Slot (up to 512GB) *power supply is not included;Motion Detection 2.0	197
YENİ DS-2CD1T47G2H-LIUF/SL (Dahili mikrofon) ColorVu		4MP ColorVu & Smart Hybrid Light Bullet Network Kamera 1/3" Progressive CMOS, ICR,2560 × 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, DWDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; IR and white light, up to 50m *-F: SD Card Slot (up to 512GB) *power supply is not included;Motion Detection 2.0	212
YENİ DS-2CD1047G3-LIUF ColorVu 3.0		4MP ColorVu 3.0 & Smart Hybrid Light Bullet Network Kamera 1/3" Progressive CMOS, ICR, 2560 × 1440: 25fps(P)/24fps(N), H.265+/H.265/H.264+/H.264, WDR, 3D DNR, BLC, HLC, Smart hybrid light, IR or white light range: up to 30m, DC12V & PoE power supply, Support remote mobile management via Hik-Connect; *-LIUF: added built-in SD card slot and support up to 512GB SD card;	208
YENİ DS-2CD1347G3-LIUF ColorVu 3.0		4MP ColorVu 3.0 & Smart Hybrid Light Turret Network Kamera 1/3" Progressive CMOS, ICR, 2560 × 1440: 25fps(P)/24fps(N), H.265+/H.265/H.264+/H.264, WDR, 3D DNR, BLC, HLC, Smart hybrid light, IR or white light range: up to 30m, DC12V & PoE power supply, Support remote mobile management via Hik-Connect; *-LIUF: added built-in SD card slot and support up to 512GB SD card;	208
YENİ DS-2CD1047G3-LIUF/SL ColorVu 3.0		4MP ColorVu 3.0 & Smart Hybrid Light Bullet Network Kamera 1/3" Progressive CMOS, ICR, 2560 × 1440: 25fps(P)/24fps(N), H.265+/H.265/H.264+/H.264, WDR, 3D DNR, BLC, HLC, Smart hybrid light, IR or white light range: up to 30m, DC12V & PoE power supply, Support remote mobile management via Hik-Connect; *-LIUF/SL: added built-in SD card slot and support up to 512GB SD card, built-in speaker to support two-way audi	219
YENİ DS-2CD1347G3-LIUF/SL ColorVu 3.0		4MP ColorVu 3.0 & Smart Hybrid Light Turret Network Kamera 1/3" Progressive CMOS, ICR, 2560 × 1440: 25fps(P)/24fps(N), H.265+/H.265/H.264+/H.264, WDR, 3D DNR, BLC, HLC, Smart hybrid light, IR or white light range: up to 30m, DC12V & PoE power supply, Support remote mobile management via Hik-Connect; *-LIUF/SL: added built-in SD card slot and support up to 512GB SD card, built-in speaker to support two-way audi	219
DS-2CD1643G2-LIZSU (Dahili mikrofon)		4MP Smart Hybrit Light Motorize Varifokal Lensli Bullet Kamera 120dB WDR 1/3" Progressive CMOS, ICR, 2560 × 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect;*-S: alarm and audio;*power supply is not included ;Motion Detection 2.0	259








ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-2CD1743G2-LIZSU (Dahili mikrofon)		4MP Smart Hybrit Light Motorize Varifokal Lensli Dome Kamera 120dB WDR 1/3" Progressive CMOS, ICR, 2560 × 1440: 20fps(P)/(N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect;*-S: alarm and audio; *power supply is not included	259
DS-2CD2043G2-LI2U (Dahili mikrofon)		4M Smart Hybrit Light Bullet Network Kamera Acusens & Full-Metal & VCA & 120DB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-2U:Built-in Dual-Array Microphone	255
DS-2CD2143G2-LIS2U (Dahili mikrofon)		4M Smart Hybrit Light Dome Network Kamera Acusens & Full Metal & VCA & 120DB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-S model: Audio/Alarm IO * -2U:Built-in Dual-Array Microphone	255
YENİ			
DS-2CD2643G2-LIZS2U/SL		4 MP Acusense Strobe Light and Audible Warning & Smart Hybrid Light Motorized Varifocal Bullet Network Camera High quality imaging with 4 MP resolution AcuSense: Focus on person and vehicle classification based on deep learning Smart Hybrid Light: Integrates IR and White lights, 3 supplemental lighting modes Built-in Arrayed dual-microphone for real-time high quality audio security Clear imaging against strong back light due to 120 dB true WDR technology Efficient H.265+ compression technology Motorized varifocal lens for easy installation and monitoring Water and dust resistant (IP67) and vandal-resistant (IK10)	460
YENİ			
DS-2CD2743G2-LIZS2U/SL		4 MP Acusense Strobe Light and Audible Warning & Smart Hybrid Light Motorized Varifocal Dome Network Camera High quality imaging with 4 MP resolution AcuSense: Focus on person and vehicle classification based on deep learning Smart Hybrid Light: Integrates IR and White lights, 3 supplemental lighting modes Built-in arrayed dual-microphone for real-time high quality audio security Clear imaging against strong back light due to 120 dB true WDR technology Efficient H.265+ compression technology Motorized varifocal lens for easy installation and monitoring Water and dust resistant (IP67) and vandal-resistant (IK10) Active strobe light and audio alarm to warn intruders off	460







ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
<p>YENİ</p> <p>DS-2CD2147G3-LIS2UY</p> <p>ColorVu 3.0</p>		<p>4 MP Smart Hybrid Light with ColorVu Fixed Dome Network Camera HikAI-ISP for excellent noise reduction effect 24/7 colorful imaging via ColorVu technology Scene-adaptive WDR Focus on Person and Vehicle classification based on deep learning -S2U: Built-in arrayed dual-microphone for real-time high quality audio security Anti-corrosion design, providing reliability and longevity compared to standard (NEMA4X) Smart Hybrid Light: Integrates IR and White lights, 3 supplemental lighting modes Water and dust resistant (IP67) and vandal-resistant (IK10)</p>	376
<p>YENİ</p> <p>DS-2CD2047G3-LI2UY/SL (Darkfighter)</p> <p>ColorVu 3.0</p>		<p>4 MP Smart Hybrid Light with ColorVu Fixed Mini Bullet Network Camera HikAI-ISP for excellent noise reduction effect 24/7 colorful imaging via ColorVu technology Scene-adaptive WDR Focus on Person and Vehicle classification based on deep learning Built-in arrayed dual-microphone for real-time high quality audio security Provide real-time security via built-in two-way audio Anti-corrosion design, providing reliability and longevity compared to standard (NEMA4X) Smart Hybrid Light: Integrates IR and White lights, 3 supplemental lighting modes Water and dust resistant (IP67) Active strobe light and audio alarm to warn intruders off</p>	353
<p>YENİ</p> <p>DS-2CD2347G3-LIS2UY/SL (Darkfighter)</p> <p>ColorVu 3.0</p>		<p>4M ColorVu + Smart Hybrid Turret Network Kamera Live Guard & Acusens & Full Metal & VCA &120DB WDR 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 Lux @ (F1.0, AGC ON),0 Lux with light 25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 30m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone</p>	365
<p>YENİ</p> <p>DS-2CD2647G3-LI2S2UY/SL (Darkfighter)</p> <p>ColorVu 3.0</p>		<p>4MP Colorvu Motorize Varifokal Lensli Hybrid Light Bullet Kamera (H.265+) Acusens & Full Metal & VCA120dB WDR 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008Lux @ (F1.2, AGC ON),0 Lux with light 25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; /:SL Live Guard</p>	718
<p>YENİ</p> <p>DS-2CD2747G3T-LIZSY (Darkfighter)</p> <p>ColorVu 3.0</p>		<p>4MP Motorize Varifokal Lensli Smart Hybrid Light Dome Kamera Acusens & Full Metal & VCA 120dB WDR 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light 25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;</p>	688








ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-2CD2543G2-LIS2U (Dahili mikrofon)		4M Smart Hybrit Light Dome Network Kamera Acusens & Full Metal & VCA &120DB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;3000K Warm LED; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;*-S model: Audio/Alarm IO * -2U:Built-in Dual-Array Microphone	277
YENİ			
DS-2CD2T43G2-LIS2U/SL (Dahili mikrofon)		4M Smart Hybrit Light Bullet Network Kamera Acusens & Full Meal & VCA &120DB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service *-2LI/4LI model: 3000K Warm LED; EXIR, up to 60m/80m * -2U:Built-in Dual-Array Microphone	270
YENİ			
DS-2CD2046G2H-12U/SL (Powered by Darkfighter)		4M Darkfight Bullet Network Kamera Live Gaurd & Acusens & Full Metal & VCA &120DB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.001 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone;-/SL: live-guard	293
DS-2CD2146G2H-ISU (Powered by Darkfighter)		4M Darkfight Dome Network Kamera Acusens & Full Metal & VCA &120DB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.001 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 30 m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone	293
YENİ			
DS-2CD2T46G2H-IS2U/SL (Powered by Darkfighter)		4M Darkfight Bullet Network Kamera Live Gaurd Acusens & Full Metal & VCA &120DB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.001 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-2I/4I model: up to 60m(2Leds)/80m(4Leds) IR distance	327
YENİ			
DS-2CD2T47G3-LIS2UY/SL (Darkfighter) ColorVu 3.0		4M ColorVu + Smart Hybrid Bullet Network Kamera Live Gaurd & Acusens & Full Metal & VCA &120DB WDR 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 Lux @ (F1.0, AGC ON),0 Lux with light 25fps/30fps(2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;	437
DS-2CD2643G2-LIZS2U (Dahili mikrofon)		4MP Motorize Varifokal Lensli Smart Hybrid Light Bullet Kamera Acusens & Full Metal & VCA &120DB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 60m; Audio/Alarm IO; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm IO; Built-in Dual-Array Microphone	441







ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-2CD2743G2-LIZS2U (Dahili mikrofon)		4MP Motorize Varifokal Lensli Hybrid Light Bullet Kamera Acusens & Full Metal & VCA&120dB WDR 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 Lux @ (F1.6, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service *-2LI/4LI model: 3000K Warm LED; EXIR, up to 60m/80m * -2U:Built-in Dual-Array Microphone	441
DS-2CD2646G2HT-IZS (Powered by Darkfighter)		4MP Motorize Varifokal Lensli IR Bullet Kamera (H.265+) Acusens & Full Metal & VCA120dB WDR 1/3" Progressive Scan CMOS((C) model); H.265+/H.265/H.264+/H.264/MJPEG; Powered by Darkfighter technology,Color: 0.003 lux @(F1.4, AGC ON), 0 lux with IR; 25fps/30fps(2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm I/O *non-(C) model:1/2.7" Progressive Scan CMOS	521
YENİ			
DS-2CD2746G2H-IPTRZS (Powered by Darkfighter)		4MP PTRZ Motorize Varifokal Lensli IR Dome Kamera (H.265+) Acusens & Full Metal & VCA120dB WDR & PTRZ 1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.001 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/30fps (2688 × 1520, 1920 × 1080, 1280 × 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;	608
YENİ			
iDS-2CD2T47G2/V-XS Perimeter Protection AI camera		4MP DeepinViewX Fixed Lens Bullet Camera for Perimeter Protection Darkfighter2.0 Ultra-low light technology,Color:0.0003Lux/F1.0 BW:0.0001Lux/F1.0 1/1.8"CMOS;4MP 50fps/60fps H.265+/H.265/H.264+/H.264/MJPEG;120dB WDR 3 Steams 1*Audio Out,1*Audio In;1*Built in MIC;1*Built in Speaker 1*Alarm In, 1*Alarm Out;DC12V Output RS485 IP67, IK10 -30 ° C to 60 ° C (-22 ° F to 140 ° F) ONVIF Profile G/S/T/M;Perimeter Detection by Guanlan large model, VCA range up to 80m in daytime, 60m in night time.	699
6MP IP KAMERA			
DS-2CD1063G2-LIUF (Dahili mikrofon)		6MP Mini IR Bullet Kamera Smart Hybrid Light High quality imaging with 6 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Water and dust resistant (IP67); Efficient H.265+ compression technology; Support on-board storage up to 256 GB (SD card slot) (Optional); Motion detection 2.0	172
DS-2CD1363G2-LIUF (Dahili mikrofon)		6MP Turret Kamera Smart Hybrid Light & Motion Detection 2.0 High quality imaging with 6 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Water and dust resistant (IP67); Efficient H.265+ compression technology; Support on-board storage up to 256 GB (SD card slot) (Optional);	172
YENİ			
DS-2CD1T63G2-LIUF/SL (Dahili mikrofon)		6MP Bullet Kamera Smart Hybrid Light & Motion Detection 2.0 & Live Guard 1/3" Progressive CMOS, ICR,3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone & speaker, audio & strobe light alarm, DC12V & PoE, Support mobile monitoring via Hik-Connect; *power supply is not included	193






ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
YENİ DS-2CD1063G2-LIUF/SL		6MP Mini IR Bullet Kamera Smart Hybrid Light High quality imaging with 6 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Water and dust resistant (IP67); Efficient H.265+ compression technology; Support on-board storage up to 256 GB (SD card slot) (Optional); Motion detection 2.0 /SL: Live-guard	179
YENİ DS-2CD1363G2-LIUF/SL		6MP Mini IR Turret Kamera Smart Hybrid Light High quality imaging with 6 MP resolution; Support Human and Vehicle Detection; Smart Hybrid Light: advanced technology with long range; Water and dust resistant (IP67); Efficient H.265+ compression technology; Support on-board storage up to 256 GB (SD card slot) (Optional); Motion detection 2.0 /SL: Live-guard	179
DS-2CD1067G2H-LIUF (Dahili mikrofon) 		6MP Mini Bullet Kamera (H.265+) ColorVu & Smart Hybrid Light & Motion Detection 2.0 1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; *-F: SD Card Slot (up to 512GB) *power supply is not included	197
DS-2CD1367G2H-LIUF (Dahili mikrofon) 		6MP Mini Bullet Kamera ColorVu & Smart Hybrid Light & Motion Detection 2.0 1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; *-F: SD Card Slot (up to 512GB) *power supply is not included	197
YENİ DS-2CD1T67G2H-LIUF/SL (Dahili mikrofon) 		6MP Mini Bullet Kamera (H.265+) ColorVu & Smart Hybrid Light & Motion Detection 2.0 & Live Guard 1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 30m, Built-in microphone, DC12V & PoE, Support mobile monitoring via Hik-Connect; 50 m IR *-F: SD Card Slot (up to 512GB) /SL: live Guard	245
YENİ DS-2CD1067G3-LIUF 		6 MP ColorVu 3.0 Fixed Bullet Network Camera 1/2.4" Progressive CMOS, ICR, 3200 × 1800: 20fps(P)/fps(N), H.265+/H.265/H.264+/H.264, WDR, 3D DNR, BLC, HLC, Smart hybrid light, IR or white light range: up to 30m, DC12V & PoE power supply, Support remote mobile management via Hik-Connect; *-LIUF: added built-in SD card slot and support up to 512GB SD card;	234
YENİ DS-2CD1367G3-LIUF 		6 MP ColorVu 3.0 Fixed Turret Network Camera 1/2.4" Progressive CMOS, ICR, 3200 × 1800: 20fps(P)/fps(N), H.265+/H.265/H.264+/H.264, WDR, 3D DNR, BLC, HLC, Smart hybrid light, IR or white light range: up to 30m, DC12V & PoE power supply, Support remote mobile management via Hik-Connect; *-LIUF: added built-in SD card slot and support up to 512GB SD card;	234
YENİ DS-2CD1067G3-LIUF/SRB 		6 MP ColorVu 3.0 LiveGuard Fixed Bullet Network Camera 1/2.4" Progressive CMOS, ICR, 3200 × 1800: 20fps(P)/fps(N), H.265+/H.265/H.264+/H.264, WDR, 3D DNR, BLC, HLC, Smart hybrid light, IR or white light range: up to 30m, DC12V & PoE power supply, Support remote mobile management via Hik-Connect; *-LIUF/SRB: added built-in speaker to support two-way audio and audio alarm, built-in red and blue strobe alarm light;	245







ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
YENİ			
DS-2CD1367G3-LIUF/SRB ColorVu 3.0		6 MP ColorVu 3.0 LiveGuard Fixed Turret Network Camera 1/2.4" Progressive CMOS, ICR, 3200 × 1800: 20fps(P)/fps(N), H.265+/H.265/H.264+/H.264, WDR, 3D DNR, BLC, HLC, Smart hybrid light, IR or white light range: up to 30m, DC12V & PoE power supply, Support remote mobile management via Hik-Connect; *-LIUF/SRB: added built-in speaker to support two-way audio and audio alarm, built-in red and blue strobe alarm light;	245
DS-2CD1663G2-LIZSU (Dahili mikrofon)		6MP Smart Hybrit Light Motorize Varifokal Lensli Bullet Kamera (H.265+) 120dB WDR 1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect *-S: alarm and audio	266
DS-2CD1763G2-LIZSU (Dahili mikrofon)		6MP Smart Hybrit Light Motorize Varifokal Lensli Dome Kamera (H.265+) 120dB WDR 1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect *-S: alarm and audio	266
YENİ			
DS-2CD1663G2-LIZSU/SL		6 MP Dual Light MD 2.0 Varifokal Bullet Network Camera 1/3" Progressive CMOS, ICR, 3200 × 1800: 20fps(P/N), H.265+/H.265/H.264+&H.264, WDR, 3D DNR, BLC, IR or white light range: up to 50m, Built-in microphone & speaker, audio & strobe light alarm, SD Card Slot (up to 256GB), DC12V & PoE, Support mobile monitoring via Hik-Connect *-S: alarm and audio /SL: live Guard	281
8MP IP KAMERA			
DS-2CD2083G2-LI2U (Dahili mikrofon)		8M Smart Hybrit Light Mini Bullet Camera Acusens & Full Metal & VCA & 120DB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200x1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;3000K Warm LED; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; * -2U:Built-in Dual-Array Microphone	304
YENİ			
DS-2CD2083G2-LI2U/SL		8M Smart Hybrit Light Mini Bullet Camera Acusens & Full Metal & VCA & 120DB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200x1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;3000K Warm LED; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; * -2U:Built-in Dual-Array Microphone /SL: live Guard	327
YENİ			
DS-2CD2783G2-LIZS2U/SL		8MP Motorize Varifokal Lensli Hybrid Light Dome Kamera Acusens & Full Metal & VCA&120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200x1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm IO; Built-in Dual-Array Microphone and Speaker /SL: Live Guard	574





ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
		YENİ	
DS-2CD2683G2-LIZS2U/SL		8MP Motorize Varifokal Lensli Hybrid Light Bullet Kamera Acusens & Full Metal & VCA&120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200x1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm IO; Built-in Dual-Array Microphone and Speaker /SL: Live Guard	574
		YENİ	
DS-2CD2187G3-LIS2UY		8M ColorVu+ Hybrid Dome Camera Acusens & Full Metal & VCA &120DB WDR "1/1.8"" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 Lux @ (F1.0, AGC ON),0 Lux with light 25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 30m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Anti-Corrosion;"	422
DS-2CD2183G2-LIS2U (Dahili mikrofon)		8M Smart Hybrit Light Dome Camera Acusens & Full Metal & VCA &120DB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200x1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED;EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-S model: Audio/Alarm IO * -2U:Built-in Dual-Array Microphone	319
DS-2CD2583G2-LI2U (Dahili mikrofon)		8M Smart Hybrit Light Mini Dome Camera Acusens & Full Metal & VCA &120DB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200x1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR;3000K Warm LED; EXIR, up to 30m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-S model: Audio/Alarm IO * -2U:Built-in Dual-Array Microphone	338
		YENİ	
DS-2CD2T83G2-LIS2U/SL (Dahili mikrofon)		8M Smart Hybrit Light Bullet Camera Acusens & Full Metal & VCA &120DB WDR & live guard 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200x18:00, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-2LI/4LI model: 3000K Warm LED; EXIR, up to 60m/80m * -2U:Built-in Dual-Array Microphone	350
		YENİ	
DS-2CD2086G2H-I2U/SL (Darkfighter)		8M Darkfight mini Bullet Camera Acusens & Full Metal & VCA &120DB WDR & Live Guard 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 40 m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone	372







ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-2CD2186G2H-ISU (Darkfighter)		8M Darkfight Dome Camera Acusens & Full Metal & VCA &120DB WDR 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR, Up to 30 m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone	372
YENİ			
DS-2CD2T86G2H-IS2U/SL (Darkfighter)		8M Darkfight Bullet Camera Acusens & Full Metal & VCA &120DB WDR & Live Guard 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light; 25fps/24fps(3840×2160);25fps/30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720) ; VCA functions; 3 streams; 3D DNR; BLC; ICR; EXIR; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *-2I/4I model: up to 60m(2Leds)/80m(4Leds) IR distance	452
YENİ			
DS-2CD2087G3-LI2UY/SL (Darkfighter)		8M ColorVu+ Hybrid mini Bullet Camera Acusens & Full Metal & VCA &120DB WDR & Live Guard 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 Lux @ (F1.0, AGC ON),0 Lux with light 25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone	437
YENİ			
DS-2CD2387G3-LIS2UY/SL (Darkfighter)		8M ColorVu+ Hybrid Dome Camera Acusens & Full Metal & VCA &120DB WDR & Live Guard 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light 25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 30m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; -U:Built-in micphone	437
YENİ			
DS-2CD2T87G3-LIS2UY/SL (Darkfighter)		8M ColorVu+ Hybrid Bullet Camera Acusens & Full Metal & VCA &120DB WDR & Live Guard 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.0, AGC ON),0 Lux with light 25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;	521
YENİ			
DS-2CD2683G2-LIZS2U (Power By Darkfighter)		8MP Motorize Varifokal Lensli Hybrid Light Bullet Kamera Acusens & Full Metal & VCA&120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200x1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 60m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm IO; Built-in Dual-Array Microphone	540
YENİ			
DS-2CD2783G2-LIZS2U (Power By Darkfighter)		8MP Motorize Varifokal Lensli Hybrid Light Dome Kamera Acusens & Full Metal & VCA&120dB WDR 1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux@(F1.6, AGC ON), 0 lux with IR; 20fps(3840×2160), 25fps/30fps (3200x1800, 2688×1520, 1920×1080); VCA functions; 3 streams; 3D DNR; BLC/HLC; ICR; 3000K Warm LED; EXIR, up to 40m; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Audio/Alarm IO; Built-in Dual-Array Microphone	540











ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
YENİ DS-2CD2686G2HT-IZS2U/SL (Darkfighter)		8MP Motorize Varifokal Lensli IR Bullet Kamera Acusens & Full Metal & VCA120dB WDR & Live Guard 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light 25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *Junction box is included in the camera package	680
YENİ DS-2CD2786G2H-IPTRZS (Darkfighter)		8MP Motorize Varifokal Lensli IR Dome Kamera Acusens & Full Metal & VCA120dB WDR & PTRZ 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light 25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; *Junction box is included in the camera package	722
YENİ DS-2CD2687G3-LIZS2UY/SL (Darkfighter) ColorVu 3.0		8MP Colorvu Motorize Varifokal Lensli Hybrid Light Bullet Kamera Acusens & Full Metal & VCA&120dB WDR & Live Guard 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light 25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;	790
YENİ DS-2CD2787G3T-LIZSY (Darkfighter) ColorVu 3.0		8MP Colorvu Motorize Varifokal Lensli Hybrid Light Dome Kamera Acusens & Full Metal & VCA&120dB WDR 1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0008 Lux @ (F1.2, AGC ON),0 Lux with light 25fps/24fps(3840 × 2160, 3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720); VCA functions; 3 streams; 3D DNR; BLC; ICR; 3000K Warm LED;IR, up to 40m DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service;	756
Panoramic & Live Guard Cameras			
YENİ DS-2CD2T46G2P-ISU/SL		2*4MP Panoramic & Live Guard Cameras Strobe light & Audio 2*1/2.5" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.003 lux @(F1.6, AGC ON), 0 lux with IR; 20fps(3632×1632),VCA functions; 2 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Built-in microphone and speaker, Audio/Alarm I/O; 180° FOV	300
YENİ DS-2CD2T47G2P-LSU/SL ColorVu		2 4MP Colorvu Panoramic & Live Guard Cameras 2*1/1.8" Progressive Scan CMOS; Strobe light & Audio H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on; 20fps(5120×1440),VCA functions; 2 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK-Connect cloud service; Built-in microphone and speaker, Audio/Alarm I/O;180° FOV	407










ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
YENİ			
DS-2CD2T87G2P-LSU/SL ColorVu		2 8MP ColorVu Panoramic & Live Guard Cameras Strobe light & Audio 2*1/1.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.0005 lux @(F1.0, AGC ON), 0 lux with LED on; 20fps(5120×1440),VCA functions; 2 streams; 3D DNR; BLC; ICR; 3000K Warm LED; DC12V&PoE; Built-in micro SD/SDHC/SDXC slot; HIK- Connect cloud service; Built-in microphone and speaker, Audio/Alarm I/O; 180° FOV	471
Balıkgözü KAMERA			
DS-2CD2955G0-ISU		5MP Balıkgözü KAMERA 1/2.9" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.016 lux@(F2.2, AGC ON), 0 lux with IR; 25fps/30fps(2560×1920, 2048×1536, 1920×1080); F2.2, field of view: 180°(H)x180°(V); 120dB WDR; 2 streams; 3D DNR; BLC; ICR; EXIR, up to 8m; DC12V&PoE; Built- in micro SD/SDHC/SDXC slot; HIK-Connect cloud service build-in-mic	361
HeatPro Termal KAMERA			
HM-TD2618-7/G0/T1A HeatPro		Thermal & Optical Bi-spectrum Network Bullet Camera 160 × 120 resolution, 12 μm, VOx UFPA, NETD ≤25 mK (25°C, F1.0) Video content analysis 3.0 (VCA3.0): high accuracy vehicle/human detection and classification Support smart hybrid light: white light, IR and smart mode Temperature exception alarm, -20 °C to 150 °C (-4 °F to 302 °F), ± 8°C (± 14.4°F) Support fire point detection algorithm Support smoking detection algorithm Image processing technology: linear, histogram, self-adaptive thermal AGC mode, DDE, 3D DNR	923
HM-TD2618-3/G0/T1A HeatPro		Thermal & Optical Bi-spectrum Network Bullet Camera 160 × 120 resolution, 12 μm, VOx UFPA, NETD ≤ 25 mK (25°C, F1.0) Video content analysis 3.0 (VCA3.0): high accuracy vehicle/human detection and classification Support smart hybrid light: white light, IR and smart mode Temperature exception alarm, -20 °C to 150 °C (-4 °F to 302 °F), ± 8°C (± 14.4°F) Support fire point detection algorithm Support smoking detection algorithm Image processing technology: linear, histogram, self-adaptive thermal AGC mode, DDE, 3D DNR	863
HM-TD2628-3/G1/T3A HeatPro		Thermal & Optical Bi-spectrum Network Bullet Camera 256 × 192 resolution, 12 μm, VOx UFPA, NETD ≤25 mK (25°C, F1.0) Extended human/vehicle detection distance and ultra low false alarm with GUANLAN Large-Scale AI Model Support smart hybrid light: white light, IR and smart mode Temperature exception alarm, -20 °C to 150 °C (-4 °F to 302 °F), ± 8°C (± 14.4°F) Support fire point detection algorithm Support smoking detection algorithm Image processing technology: linear, histogram, self-adaptive thermal AGC mode, DDE, 3D DNR	950
PTZ KAMERALAR			










ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
IP PTZ KAMERA			
DS-2DE2C400MWG-E		4 MP Network IR 2-inch PT Dome (H.265+, 30m IR) 1/2.7" Progressive Scan CMOS Color: 0.01 Lux @(F1.2, AGC ON), B/W: 0 Lux with IR 2.8 mm, horizontal FOV 94°, vertical FOV 49°, diagonal FOV 114° 4 mm, horizontal FOV 70°, vertical FOV 35°, diagonal FOV 85° White Light Distance: up to 30 m IR Distance: up to 30 m Digital WDR, BLC, HLC, 3D DNR, Built-in Microphone, Built-in Speaker, audible warning when alarm triggers, POE	160
DS-2DE2C400SCG-E ColorVu		4 MP Network ColorVu 2-inch live guard PT Dome (H.265+, 30m IR) 1/2.8" Progressive Scan CMOS 2560 × 1440 Color: 0.001 Lux @(F1.0, AGC ON), B/W: 0 Lux with IR 2.8 mm, horizontal FOV 105.7°, vertical FOV 57.3°, diagonal FOV 124.9° 4 mm, horizontal FOV 88.7°, vertical FOV 44.7°, diagonal FOV 107.5° White Light Distance: up to 30 m Digital WDR, BLC, HLC, 3D DNR, Built-in Microphone, Built-in Speaker	255
DS-2SE2C400MWG-E/14		4MP Dual-lens, 2 inch live guard PT Dome , 30m IR) · Capture a large area and details at the same time · Support Human and Vehicle detection · Smart Hybrid Light: advanced technology with long range · Hik-Connect cloud service and app for remote management and views of devices · Built-in microphone and speaker for real-time audio security · Built-in memory card slot, support microSD/SDHC/SDXC card, up to 512 GB · Water and dust resistant (IP66)	255
YENİ			
DS-2SE3C404MWG-E/14(F0)		4MP Dual-lens, 2 inch live guard PTZ Dome , 30m IR) · Captures a large area and great details at the same time · High quality imaging with 4 MP resolution · Excellent low-light performance with powered-by-DarkFighter technology · Secures an expansive area with 4× optical zoom and 16× digital zoom · Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus · Supports 12V DC & PoE+ · Support Human and Vehicle Detection	471
DS-2DE4215IWG1-E		2MP Network Dış Ortam IR PTZ Kamera, Deep learning 1/2.8" progressive scan CMOS High quality imaging with 2 MP resolution. Excellent low-light performance with powered-by-DarkFighter technology. 15× optical zoom and 16× digital zoom provide close up views over expansive areas. WDR, HLC, BLC, 3D DNR, defog, EIS, regional exposure, regional focus Expansive night view with up to 100 m IR distance Support H.265+/H.265 video compression	654
DS-2DE4425IWG1-E		4MP Network Dış Ortam IR PTZ Kamera 1/2.8" progressive scan CMOS. High quality imaging with 4 MP resolution. Excellent low-light performance with powered-by-DarkFighter technology. 25× optical zoom and 16× digital zoom provide close up views over expansive areas WDR, HLC, BLC, 3D DNR, defog, EIS, regional exposure, regional focus Expansive night view with up to 100 m IR distance Support H.265+/H.265 video compression	882










ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-2SE4C425MWG-E/RB/14 ColorVu		<p>4MP Bullet lens:4MP, 30m White Light PTZ lens</p> <p>Captures a large area and great details at the same time</p> <ul style="list-style-type: none"> · High quality imaging with 4 MP resolution · Focuses on human and vehicle targets classification based on deep learning · Excellent low-light performance with powered-by-DarkFighter technology and ColorVu technology · Secures an expansive area with 25 × optical zoom and 16 × digital zoom · Expansive night view with up to 100 m IR distance & 30 m white light · Build-in speaker and dual-microphone for real-time high quality audio security · Active strobe light and audio alarm to warn intruders off · Supports 12 VDC & PoE+ 	1026
DS-2SE4C425MWG-E/26(F0) ColorVu		<p>4MP Network Dış Ortam IR PTZ Kamera</p> <p>Captures a large area and great details at the same time</p> <p>High quality imaging with 4 MP resolution</p> <p>Excellent low-light performance with powered-by-DarkFighter technology</p> <p>Secures an expansive area with 25× optical zoom and 16× digital zoom</p> <p>Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus, rapid focus</p> <p>Expansive night view with up to 200 m IR distance</p> <p>Supports 24 VAC & Hi-PoE</p> <p>Active strobe light and audio alarm to warn intruders off</p>	1060
DS-2DE7A432MWG-EB		<p>4MP Network Dış Ortam IR PTZ Kamera, Deep learning</p> <p>1/1.8" progressive scan CMOS</p> <p>Up to 2560 × 1440@30fps resolution</p> <p>Min. illumination:</p> <p>Color: 0.0005 Lux @(F1.2, AGC ON)</p> <p>B/W: 0.0001 Lux @(F1.2, AGC ON)</p> <p>0 Lux with IR</p> <p>32× optical zoom, 16× digital zoom</p> <p>WDR, HLC, BLC, 3D DNR, Defog, EIS, Regional Exposure, Regional Focus</p> <p>White light: up to 100 m / IR: up to 150 m</p> <p>24 VAC & Hi-PoE</p> <p>Support H.265+/H.265 video compression</p> <p>Support audio visual alarm</p>	1478
YENİ			
DS-2SE7C432MWG-EB ColorVu		<p>4MP Network Dış Ortam IR PTZ Kamera (32X, 200m IR, IP66, deep learning)</p> <p>Captures a large area and great details at the same time</p> <p>High quality imaging with 4 MP resolution</p> <p>Excellent low-light performance with powered-by-DarkFighter technology</p> <p>Secures an expansive area with 32× optical zoom and 16× digital zoom</p> <p>Supports WDR, HLC, BLC, 3D DNR, defog, regional exposure, regional focus, rapid focus</p> <p>Expansive night view with up to 200 m IR distance</p> <p>Supports 24 VAC & Hi-PoE</p> <p>Active strobe light and audio alarm to warn intruders off</p>	1623






ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
YENİ			
DS-2SE7C432MWG-EB/26(F0)		<p>4MP Network Dış Ortam IR PTZ Kamera (32X, 200m IR, IP66, deep learning)</p> <ul style="list-style-type: none"> · Panoramic channel supports image stitching, with 180° horizontal field of view · High quality imaging with 6 MP resolution in panoramic channel and 4 MP resolution in PTZ channel · Secures an expansive area with 32 × optical zoom and 16 × digital zoom · AcuSense technology focuses on human and vehicle targets classification and supports face capture to detect, capture and select faces in motion · Expansive night view with up to 200 m IR distance in PTZ channel and 30 m white light in panoramic channel · Active strobe light and audio alarm to warn intruders off · Smart-linkage between panoramic channel and PTZ channel 	1672
WIFI Kamera			
YENİ			
DS-2CV2Q21G1-IDW		<p>2MP Wi-Fi Indoor PT camera</p> <p>1/2.8" Progressive CMOS, ICR, 1920×1080: 25fps(P)/30fps(N), H.265+/H.265, 3D DNR, support on-board storage up to 256GB, Build-in microphone and speaker, two-way talk, support two-way audio, Support mobile monitoring via Hik-Connect 5VDC power supply is included.</p>	95
YENİ			
DS-2CD2423G2-IW		<p>2MP Wi-Fi Cube Camera</p> <p>1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0 lux with IR; 25Fps/30fps(1920×1080); 2 streams; DWDR; 3D DNR; ICR; EXIR, up to 10m; support AI human body detection; support on-board storage up to 512GB(SD card slot), Hik-Connect cloud service, Build-in microphone and speaker; Built-in 2.4G Wi-Fi, 802.11b/g/n; 12VDC & PoE power supply. *SD card is not included. *Power supplier is not included</p>	95
YENİ			
DS-2CD2443G2-IW		<p>4MP Wi-Fi Cube Camera</p> <p>1/2.8" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0 lux with IR; 20Fps(2560×1440); 2 streams; DWDR; 3D DNR; ICR; EXIR, up to 10m; support AI human body detection; support on-board storage up to 512GB(SD card slot), Hik-Connect cloud service, Build-in microphone and speaker; Built-in 2.4G Wi-Fi, 802.11b/g/n; 12VDC & PoE power supply. *SD card is not included. *Power supplier is not included</p>	117
Solar Kamera			
YENİ			
DS-2CFSP4/4G		<p>4MP 4G AOV Solar PT Camera</p> <p>1/2.9" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.01 lux @(F1.6, AGC ON), 0 lux with LED on; 12.5fps/15fps(2560×1440, 1920×1080); 2 streams; 3D DNR; BLC; ICR; EXIR LED; Solar panel & 5VDC;; Built-in memory card slot, support microSD/SDHC/SDXC card up to 256 GB; Build-in microphone and speaker; Support working between 0 °C to 45 °C (32 °F to 113 °F); Hik-Connect cloud service;</p>	300
YENİ			
DS-2CFS04/4G		<p>4MP 4G AOV Solar bullet Camera</p> <p>1/3" Progressive Scan CMOS; H.265+/H.265/H.264+/H.264/MJPEG; Color: 0.005 lux @(F1.6, AGC ON), 0 lux with LED on; 12.5fps/15fps(2560×1440, 1920×1080); 2 streams; 3D DNR; BLC; ICR; EXIR LED; Solar panel & 5VDC;; Built-in memory card slot, support microSD/SDHC/SDXC card up to 512 GB; Build-in microphone and speaker; Support working between 0 °C to 45 °C (32 °F to 113 °F); Hik-Connect cloud service;</p>	217

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
NETWORK VİDEO KAYIT CİHAZLARI			
4 KANAL NVR			
DS-7104NI-Q1		4 Kanal Q Serial mini NVR (1 SATA, H.265) 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, mini 1U case(Plastic)	135
DS-7104NI-Q1/4P		4 Kanal Q serial mini NVR (1 SATA, H.265, POE) 40Mbps Bit Rate Input Max (up to 4-ch IP video) 1 SATA interface, 4 independent PoE network interfaces, mini 1U case(Plastic)	215
DS-7104NI-Q1/M		4 Kanal Q serial mini NVR (1 SATA, H.265) 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interface, mini 1U case(Metal)	146
DS-7104NI-Q1/4P/M		4 Kanal Q serial mini NVR (1 SATA, H.265, POE) 40Mbps Bit Rate Input Max (up to 4-ch IP video) 1 SATA interface, 4 independent PoE network interfaces, mini 1U case(Metal)	230
DS-7604NI-Q1		4 Kanal Q serial NVR (1 SATA, H.265) 4-channels Motion Detection 2.0 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 315 1U case	204
DS-7604NI-Q1/4P		4 Kanal Q serial NVR (1 SATA, H.265, POE) 4-channels Motion Detection 2.0 40Mbps Bit Rate Input Max (up to 4-ch IP video), 1 SATA interfaces, 315 1U case	299
YENİ			
DS-7604NXI-K1		4-ch 1U K Series AcuSense 4K NVR All-ch Motion Detection 2.0 Up to 1-ch false alarm reduction through human and vehicle target classification based on deep learning(upcoming) Up to 1-ch @ 12MP or 2-ch @ 8MP or 4-ch @ 4MP or 8-ch @ 1080P decoding capacity	281
YENİ			
DS-7604NXI-K1/4P		4-ch 1U K Series AcuSense 4K POE NVR Adopt Hikvision AcuSense technology to minimize manual effort and security costs Efficient playback with AcuSearch technology Accurate perimeter protection effectively reduces false alarms Automatic cameras connection and configuration Up to 4-ch IP camera inputs, plug & play with 4 Power-over-Ethernet (PoE) interfaces H.265+/H.265/H.264+/H.264 video formats Up to 3-ch@12 MP or 5-ch@8 MP or 10-ch@4 MP or 20-ch@1080p decoding capacity Up to 40 Mbps incoming bandwidth	369
8 KANAL NVR			
DS-7108NI-Q1		8 Kanal Q serial mini NVR (1 SATA, H.265) 60Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, mini 1U case(Plastic)	172
DS-7108NI-Q1/8P(D)		8 Kanal Q serial mini NVR (1 SATA, H.265, POE) 60Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, mini 1U case(Plastic)	39











ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-7108NI-Q1/M		8 Kanal Q serial mini NVR (1 SATA, H.265) 60Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interface, mini 1U case(Metal)	179
DS-7108NI-Q1/8P/M		8 Kanal Q serial mini NVR (1 SATA, H.265, POE) 60Mbps Bit Rate Input Max (up to 8-ch IP video) 1 SATA interface, 8 independent PoE network interfaces, mini 1U case(Metal)	321
DS-7608NI-Q1		8 Kanal Q serial NVR (1 SATA, H.265) 4-channels Motion Detection 2.0 80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interfaces,4 independent PoE network interfaces, 315 1U case	245
DS-7608NI-Q1/8P		8 Kanal Q serial NVR (1 SATA, H.265, POE) 4-channels Motion Detection 2.0 80Mbps Bit Rate Input Max (up to 8-ch IP video), 1 SATA interfaces,4 independent PoE network interfaces, 315 1U case	387
DS-7608NI-Q2		8 Kanal Q serial NVR (2 SATA, H.265) 4-channels Motion Detection 2.0 80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	281
DS-7608NI-Q2/8P		8 Kanal Q serial NVR (2 SATA, H.265, POE) 4-channels Motion Detection 2.0 80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case	445
YENİ			
DS-7608NXI-K1		8-ch 1U K Series AcuSense 4K NVR Adopt Hikvision AcuSense technology to minimize manual effort and security costs Efficient playback with AcuSearch technology Accurate perimeter protection effectively reduces false alarms Automatic cameras connection and configuration Up to 8-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 3-ch@12 MP or 5-ch@8 MP or 10-ch@4 MP or 20-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	314
YENİ			
DS-7608NXI-K1/8P		8-ch 1U K Series AcuSense 4K POE NVR Adopt Hikvision AcuSense technology to minimize manual effort and security costs Efficient playback with AcuSearch technology Accurate perimeter protection effectively reduces false alarms Automatic cameras connection and configuration Up to 8-ch IP camera inputs, plug & play with 8 Power-over-Ethernet (PoE) interfaces H.265+/H.265/H.264+/H.264 video formats Up to 3-ch@12 MP or 5-ch@8 MP or 10-ch@4 MP or 20-ch@1080p decoding capacity Up to 80 Mbps incoming bandwidth	496
DS-7608NXI-K2		8 kannel K series AcuSense NVR (2 SATA ,4K & H.265) All-channels Motion Detection 2.0 Facial Recognition for up to 4 channels picture stream or 1 channels video stream; * Facial recognition and Motion Detection 2.0 cannot be enabled at the same time. Support 16 face libraries, up to 20,000 face pictures in total; 80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 380 1U case, alarm I/O: 4/1	402














ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-7608NXI-K2/8P		8 kanall K series AcuSense NVR (2 SATA 4K & H.265,POE) All-channels Motion Detection 2.0 Facial Recognition for up to 4 channels picture stream or 1 channels video stream; * Facial recognition and Motion Detection 2.0 cannot be enabled at the same time. Support 16 face libraries, up to 20,000 face pictures in total; 80Mbps Bit Rate Input Max (up to 8-ch IP video), 2 SATA interfaces, 8 independent PoE network interfaces, 380 1U case, alarm I/O: 4/1	642
YENİ			
DS-7608NI-M2		8 Kanal M seral 8K NVR (2 SATA, 8K,H.265+) 8-ch 1U 8K NVR H.265+/H.265/H.264+/H.264 video formats Up to 8-ch IP camera inputs Up to 8-ch@8 MP decoding capacity Up to 128 Mbps incoming bandwidth Up to 8-ch IP speakers can be connected	715
YENİ			
DS-7608NI-M2/8P		8 Kanal M serial 8K NVR (2 SATA, 8K,H.265+ , POE) 128Mbps Bit Rate Input Max(up to 8-ch IP video),8x8MP decoding capability,HDMI up to 8K, 2 SATA Interfaces, 8 independent PoE network interfaces, alarm I/O: 4/1, 380 1U case	898
16 KANAL NVR			
DS-7616NI-Q2		16 Kanal Q serial NVR (2 SATA, H.265) 160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 380 1U case	321
DS-7616NI-Q2/16P		16 Kanal Q serial NVR (2 SATA, H.265,POE) 160Mbps Bit Rate Input Max (up to 16-ch IP video), 2 SATA interfaces, 16 independent PoE network interfaces, 380 1U case	602
YENİ			
DS-7616NXI-K1		16-ch 1U K Series AcuSense 4K NVR Adopt Hikvision AcuSense technology to minimize manual effort and security costs Efficient playback with AcuSearch technology Accurate perimeter protection effectively reduces false alarms Automatic cameras connection and configuration Up to 16-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 3-ch@12 MP or 5-ch@8 MP or 10-ch@4 MP or 20-ch@1080p decoding capacity Up to 160 Mbps incoming bandwidth	365
DS-7616NXI-K2		16 Kanal K serial Acusense NVR (2 SATA,4k&H.265) Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity; Up to 160 Mbps incoming bandwidth; Adopt Hikvision Acusense technology to minimize manual effort and security costs	482
DS-7616NXI-K2/16P		16 Kanal K serial Acusense NVR (2 SATA, 4K&H.265, POE) Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity; Up to 160 Mbps incoming bandwidth; Adopt Hikvision Acusense technology to minimize manual effort and security costs	850
YENİ			
DS-7616NI-M2		16 Kanal M serial 8K NVR (2 SATA, 8K & H.265+) 128Mbps Bit Rate Input Max(up to 8-ch IP video),8x8MP decoding capability,HDMI up to 8K, 2 SATA Interfaces, alarm I/O: 4/1, 380 1U case	814









ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
YENİ DS-7616NI-M2/16P		16 Kanal M serial 8K NVR (2 SATA, 8K,H.265+ , POE) 128Mbps Bit Rate Input Max(up to 8-ch IP video),8x8MP decoding capability,HDMI up to 8K, 2 SATA Interfaces, 8 independent PoE network interfaces, alarm I/O: 4/1, 380 1U case	1241
YENİ DS-7716NXI-K4		16-ch 1.5U K Series AcuSense 4K NVR Automatic speed control fans are designed for running quietly and energy saving Adopt Hikvision AcuSense technology to minimize manual effort and security costs Efficient playback with AcuSearch technology Accurate perimeter protection effectively reduces false alarms Automatic cameras connection and configuration Up to 16-ch IP camera inputs H.265+/H.265/H.264+/H.264 video formats Up to 3-ch@12 MP or 5-ch@8 MP or 10-ch@4 MP or 20-ch@1080p decoding capacity Up to 160 Mbps incoming bandwidth	878
32 KANAL NVR			
DS-7632NXI-K2		32 Kanal K serial Acusense NVR (2 SATA, 4K&H.265) Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity Up to 256 Mbps incoming bandwidth	650
DS-7732NXI-K4		32 Kanal K serial Acusense NVR (4SATA, 4K&H.265) Up to 2-ch@12 MP or 3-ch@8 MP or 6-ch@4 MP or 12-ch@1080p decoding capacity Up to 256 Mbps incoming bandwidth	954
DS-7732NXI-I4		32 Kanal I serial Acusense NVR (4SATA, 4K&H.265+) False alarm reduction for up to 4-ch 1080P; Facial Recognition for up to 4 channels picture stream or 1 channels video stream; * Facial recognition and perimeter protection cannot be enabled at the same time. Support 16 face libraries, up to 10,000 face pictures in total; 256Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces,2 HDMI ouputs,1 VGA port, 1 CVBS output,1 eSATA, alarm I/O: 16/9, 1.5U case,19"	1398
YENİ DS-7732NI-M4		32 Kanal M serial 8K NVR (4 SATA, 8K & H.265+) 320Mbps Bit Rate Input Max(up to 32-ch IP video), 32x2MP decoding capability, 4 SATA Interfaces, 2 HDMI ouputs(up to 8K),1 eSATA,alarm I/O: 16/9 1.5U case,19"	1398
YENİ DS-8632NXI-I8/S		32 Kanal I serial Acusense NVR (8 SATA, Raid, H.265+) 320Mbps Bit Rate Input Max(up to 32-ch IP video), 32x2MP decoding capability, 8 SATA Interfaces, 2 HDMI ouputs(up to 4K),1 eSATA,alarm I/O: 16/9 2U case,19"	2223
64 KANAL NVR			
YENİ DS-7764NI-M4		64 Kanal M serial 8K NVR (4 SATA,8K&H.265+) Up to 2-ch@32 MP/2-ch@24 MP/4-ch@12 MP/8-ch@8 MP/16-ch@4 MP/32-ch@1080p decoding capacity; Up to 400 Mbps incoming bandwidth and 400 Mbps outgoing bandwidth; 2 HDMI and 1 VGA interfaces, 8K or dual 4K video outputs	2158
YENİ DS-8664NXI-I8/S		64 Kanal I Sereil Acusense NVR (8 SATA, Raid, H.265+) 320Mbps Bit Rate Input Max(up to 64-ch IP video), 32x2MP decoding capability, 8 SATA Interfaces, 2 HDMI ouputs(up to 4K),1 eSATA alarm I/O: 16/9 2U case,19"	2991
DeepInmind NVR			









ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
YENİ			
iDS-7716NXI-M4/X		<p>16 Kanal M Sereil DeepMind NVR (4 SATA,H 265+,Deepleaning Feature, Large Model algorithm)</p> <p>256 Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, Up to 14TB per HDD,alarm I/O: 16/8, 1.5U case,19"</p> <p>Facial Recognition for up to 16 channels picture stream or 16 channels video stream;Support 16 face libraries, up to 100,000 face pictures per library and support 100,000 pictures in total.</p> <p>Video Structuralization for up to 12-ch video analysis.</p> <p>False alarm filtering for up to 16-ch behavior detection(line crossing, intrusion,region entrance and region exiting)</p>	2945
YENİ			
iDS-7732NXI-M4/X		<p>32 Kanal M Sereil DeepMind NVR (4 SATA,H 265+,Deepleaning Feature, Large Model algorithm)</p> <p>256 Mbps Bit Rate Input Max(up to 16-ch IP video), 4 SATA Interfaces, Up to 14TB per HDD,alarm I/O: 16/8, 1.5U case,19"</p> <p>Facial Recognition for up to 16 channels picture stream or 16 channels video stream;Support 16 face libraries, up to 100,000 face pictures per library and support 100,000 pictures in total.</p> <p>Video Structuralization for up to 12-ch video analysis.</p> <p>False alarm filtering for up to 16-ch behavior detection(line crossing, intrusion,region entrance and region exiting)</p>	3226
Acuseek NVR			
YENİ			
DS-7608NXI-K2/VPro		<p>8-ch 1U AcuSeek K VPro NVR</p> <p>Up to 8-ch AcuSeek and AcuSearch function</p> <p>Adopt Hikvision AcuSense technology to minimize manual effort and security costs</p> <p>Accurate perimeter protection effectively reduces false alarms</p> <p>Automatic cameras connection and configuration</p> <p>Up to 8-ch IP camera inputs</p> <p>Up to 3-ch@12 MP or 5-ch@8 MP or 10-ch@4 MP or 20-ch@1080p decoding capacity</p> <p>H.265+/H.265/H.264+/H.264 video formats</p> <p>Up to 80 Mbps incoming bandwidth</p>	718
YENİ			
DS-7608NXI-K2/8P/Vpro		<p>8-ch 1U 8 PoE AcuSeek K VPro NVR</p> <p>Up to 8-ch AcuSeek and AcuSearch function</p> <p>Adopt Hikvision AcuSense technology to minimize manual effort and security costs</p> <p>Accurate perimeter protection effectively reduces false alarms</p> <p>Automatic cameras connection and configuration</p> <p>Up to 8-ch IP camera inputs, plug & play with 8 Power-over-Ethernet (PoE) interfaces</p> <p>Up to 3-ch@12 MP or 6-ch@8 MP or 12-ch@4 MP or 24-ch@1080p decoding capacity</p> <p>H.265+/H.265/H.264+/H.264 video formats</p> <p>Up to 80 Mbps incoming bandwidth</p>	1208
YENİ			
DS-7616NXI-K2/Vpro		<p>16-ch 1U AcuSeek K VPro NVR</p> <p>Up to 16-ch AcuSeek and AcuSearch function</p> <p>Adopt Hikvision AcuSense technology to minimize manual effort and security costs</p> <p>Accurate perimeter protection effectively reduces false alarms</p> <p>Automatic cameras connection and configuration</p> <p>Up to 16-ch IP camera inputs</p> <p>Up to 3-ch@12 MP or 5-ch@8 MP or 10-ch@4 MP or 20-ch@1080p decoding capacity</p> <p>H.265+/H.265/H.264+/H.264 video formats</p> <p>Up to 160 Mbps incoming bandwidth</p>	874









ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
YENİ		16-ch 1U 16 PoE AcuSeek K VPro NVR Up to 16-ch AcuSeek and AcuSearch function Adopt Hikvision Acusense technology to minimize manual effort and security costs Accurate perimeter protection effectively reduces false alarms Automatic cameras connection and configuration Up to 16-ch IP camera inputs, plug & play with 16 Power-over-Ethernet (PoE) interfaces Up to 3-ch@12 MP or 6-ch@8 MP or 12-ch@4 MP or 24-ch@1080p decoding capacity H.265+/H.265/H.264+/H.264 video formats Up to 160 Mbps incoming bandwidth	1623
YENİ		32-ch 1U AcuSeek K VPro NVR Up to 32-ch AcuSeek and AcuSearch function Adopt Hikvision AcuSense technology to minimize manual effort and security costs Accurate perimeter protection effectively reduces false alarms Automatic cameras connection and configuration Up to 32-ch IP camera inputs Up to 3-ch@12 MP or 6-ch@8 MP or 12-ch@4 MP or 24-ch@1080p decoding capacity H.265+/H.265/H.264+/H.264 video formats Up to 256 Mbps incoming bandwidth	1189
YENİ		8-ch I/VPPro Series NVR with AcuSeek H.265+/H.265/H.264+/H.264 video formats Intelligent analytics based on Guanlan Large-Scale AI Models Up to 8-ch AcuSeek and AcuSearch function Up to 8-ch facial recognition for face picture Up to 8-ch IP camera inputs Up to 32-ch 1080p decoding capability Up to 8-ch IP speakers can be connected	1345
YENİ		8-ch I/VPPro Series NVR with AcuSeek H.265+/H.265/H.264+/H.264 video formats Intelligent analytics based on Guanlan Large-Scale AI Models Up to 8-ch AcuSeek and AcuSearch function Up to 8-ch facial recognition for face picture Up to 8-ch IP camera inputs Up to 32-ch 1080p decoding capability Up to 8-ch IP speakers can be connected	1566
YENİ		16-ch I/VPPro Series NVR with AcuSeek H.265+/H.265/H.264+/H.264 video formats Intelligent analytics based on Guanlan Large-Scale AI Models Up to 16-ch AcuSeek and AcuSearch function Up to 8-ch facial recognition for face picture Up to 16-ch IP camera inputs Up to 32-ch 1080p decoding capability Up to 8-ch IP speakers can be connected	1364
YENİ		16-ch I/VPPro Series NVR with AcuSeek H.265+/H.265/H.264+/H.264 video formats Intelligent analytics based on Guanlan Large-Scale AI Models Up to 16-ch AcuSeek and AcuSearch function Up to 8-ch facial recognition for face picture Up to 16-ch IP camera inputs Up to 32-ch 1080p decoding capability	1759
YENİ		16-ch I/VPPro Series NVR with AcuSeek H.265+/H.265/H.264+/H.264 video formats Intelligent analytics based on Guanlan Large-Scale AI Models Up to 16-ch AcuSeek and AcuSearch function Up to 8-ch facial recognition for face picture Up to 16-ch IP camera inputs Up to 32-ch 1080p decoding capability Up to 8-ch IP speakers can be connected	1881





ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
YENİ			
DS-7716NXI-I4/16P/VPro		16-ch I/Pro Series NVR with AcuSeek H.265+/H.265/H.264+/H.264 video formats Intelligent analytics based on Guanlan Large-Scale AI Models Up to 16-ch AcuSeek and AcuSearch function Up to 8-ch facial recognition for face picture Up to 16-ch IP camera inputs Up to 32-ch 1080p decoding capability Up to 8-ch IP speakers can be connected	2223
YENİ			
DS-7732NXI-I4/VPro		32-ch I/Pro Series NVR with AcuSeek H.265+/H.265/H.264+/H.264 video formats Intelligent analytics based on Guanlan Large-Scale AI Models Up to 32-ch AcuSeek and AcuSearch function Up to 8-ch facial recognition for face picture Up to 32-ch IP camera inputs Up to 32-ch 1080p decoding capability Up to 8-ch IP speakers can be connected	2158
HD-TVI ÜRÜNLER (HD-TVI PRODUCTS)			
2MP HD TVI KAMERA 4X1			
DS-2CE16D0T-EXLPF		Harici 1080p Mini IR Bullet Smart Hybrid Light Kamera High quality imaging with 2 MP, 1920 × 1080 resolution Fixed focal lens, 2.8 and 3.6 mm optional Up to 20 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging One port for 4 switchable signals (TVI/AHD/CVI/CVBS)	40
DS-2CE76D0T-EXLPF		1080p Mini IR Dome Smart Hybrid Light Kamera High quality imaging with 2 MP, 1920 × 1080 resolution Fixed focal lens, 2.8 and 3.6 mm optional Up to 20 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging One port for 4 switchable signals (TVI/AHD/CVI/CVBS)	40
DS-2CE16D0T-LPFS (Dahili mikrofon)		Harici 1080p Mini IR Bullet Smart Hybrid Light Kamera High quality imaging with 2 MP, 1920×1080 resolution 2.8 mm, 3.6 mm fixed focal lens Up to 25 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging One port for four switchable signals (TVI/AHD/CVI/CVBS) High quality audio with audio over coaxial cable, built-in mic Water and dust resistant (IP67) Smart-Hybrid light, optimize your security with flexible lighting options	47
DS-2CE76D0T-LPFS (Dahili mikrofon)		1080p Mini IR Dome Smart Hybrid Light Kamera High quality imaging with 2 MP, 1920×1080 resolution 2.8 mm, 3.6 mm fixed focal lens Up to 20 m IR distance for bright night imaging Up to 20 m white light distance for bright night imaging High quality audio with audio over coaxial cable, built-in mic One port for four switchable signals (TVI/AHD/CVI/CVBS) Smart-Hybrid light, optimize your security with flexible lighting options	47
DS-2CE10DF0T-PF 		Harici 1080p IR Bullet Kamera (ColorVu) 2M CMOS Sensor, Outdoor Bullet,0.001Lux/F1.0,0 Lux with white Light,20m,3D DNR,12 VDC,OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens,24H Color, Support TVI/AHD/CVI/CVBS video signal output	58
DS-2CE70DF0T-PF 		Harici 1080p IR Dome Kamera (ColorVu) 2M CMOS Sensor, Outdoor Bullet,0.001Lux/F1.0,0 Lux with white Light,20m,3D DNR,12 VDC,OSD Menu(Up the Coax), IP67, 2.8/3.6mm Lens,24H Color, Support TVI/AHD/CVI/CVBS video signal output	58

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
DS-2CE10DF0T-LPFS (Dahili mikrofon) 		Harici 1080p IR Bullet Kamera (ColorVu& Smart Hybrid Light) High quality imaging with 2 MP, 1920 × 1080 resolution; 24/7 color imaging with F1.0 aperture; 3D DNR technology delivers clean and sharp images; Up to 20 m white light distance for bright night imaging; Up to 20 m IR distance for bright night imaging; High quality audio with audio over coaxial cable, built-in mic; One port for four switchable signals (TVI/AHD/CVI/CVBS)	62
DS-2CE70DF0T-LPFS (Dahili mikrofon) 		Dahili/Harici 1080p IR Dome Kamera (ColorVu & Smart Hybrid Light) High quality imaging with 2 MP, 1920 × 1080 resolution; 24/7 color imaging with F1.0 aperture; 3D DNR technology delivers clean and sharp images; Up to 20 m white light distance for bright night imaging; Up to 20 m IR distance for bright night imaging; High quality audio with audio over coaxial cable, built-in mic; One port for four switchable signals (TVI/AHD/CVI/CVBS)	62
DS-2CE12DF0T-LFS (Dahili mikrofon) 		Dahili/Harici 1080p IR Bullet Kamera (ColorVu & 40m Smart Hybrid Light) 2M CMOS Sensor, Outdoor smart hybrid light Bullet, 0.001Lux/F1.0, 40m IR+40m White Light, 3D DNR, 12 VDC, Built-in Mic, Audio up Coaxial (Only TVI), OSD Menu (Up the Coax), IP67, 2.8/3.6/6mm Lens, 24H Color, Smart Lighting (With Acusense DVR), Support TVI/AHD/CVI/CVBS video signal output	84
DS-2CE18D0T-LFS		2MP Smart Hybrid Light AOC Lamp Camera (40m IR+60m White Light+ IP67) 2MP CMOS Sensor, 1080P@25fps(P)(Default)/30fps(N), EXIR, Lamp looking, 40m IR+60m White Light, Outdoor Lamp Cam, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial (Only TVI), Smart Lighting (With Acusense DVR), OSD Menu (Up the Coax), IP67, 2.8/3.6/6mm Lens, Support TVI/AHD/CVI/CVBS video signal output	84
3K(5MP 16:9) HD TVI KAMERA			
DS-2CE16K0T-LPFS (Dahili mikrofon)		Dahili/Harici 3k Hybrid Light Bullet Kamera (20mt, Metal) 3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps (Default), EXIR, 25m IR+20m White Light, Outdoor Dual-light Bullet, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial (Only TVI), Smart Lighting (With Acusense DVR), OSD Menu (Up the Coax), IP67, 2.8/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output	62
DS-2CE76K0T-LPFS (Dahili mikrofon)		Dahili/Harici 3k Hybrid Light Dome Kamera (20mt, Plastik) 3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps (Default), EXIR, 20m IR+20m White Light, indoor Dual-light Turret, ICR, 0.01 Lux/F1.2, 12 VDC, Smart IR, DNR, Built-in Mic, Audio up Coaxial (Only TVI), Smart Lighting (With Acusense DVR), OSD Menu (Up the Coax), 2.8/3.6mm Lens, Support TVI/AHD/CVI/CVBS video signal output	62
DS-2CE10KF0T-LPFS (Dahili mikrofon) 		Dahili/Harici 3k Hybrid Light Bullet Kamera 3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps (Default), Outdoor smart hybrid light mini Bullet, 0.001Lux/F1.0, 20m IR+20m White Light, 2D DNR, Built-in Mic, Audio up Coaxial (Only TVI), 12 VDC, OSD Menu (Up the Coax), IP67, 2.8/3.6mm Lens, 24H Color, Smart Lighting (With Acusense DVR), Support TVI/AHD/CVI/CVBS video signal output	84
DS-2CE70KF0T-LPFS (Dahili mikrofon) 		Dahili/Harici 3k Hybrid Light Dome Kamera 3K (5MP 16:9) CMOS Sensor, 3K @ 20 fps (Default), Indoor smart hybrid light Turret, 0.001Lux/F1.0, 20m IR+20m White Light, 2D DNR, Built-in Mic, Audio up Coaxial (Only TVI), 12 VDC, OSD Menu (Up the Coax), 2.8/3.6mm Lens, 24H Color, Smart Lighting (With Acusense DVR), Support TVI/AHD/CVI/CVBS video signal output	84

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
HD-TVI KAYIT CİHAZLARI (HD-TVI DVR)			
4 KANAL TURBO HD DVR			
DS-7104HGHI-M1		4 Kanal HD-TVI Kayıt Cihazı (1080P Lite) 4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, 1-ch IP video input, 1 SATA interface, HD1080P Lite: 25(P)/30(N) fps/ch, mini 1U case	117
YENİ			
DS-7104HGHI-M1/T		4 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio) Support HDTV I Two-way Audio technology.full-channel motion detection 2.0 ,4 Turbo HD/AHD/Analog interface input, 4-ch HDTV I coaxial video&audio input,1-ch IP video input (up to 5-ch), 1-ch RCA audio input, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, mini 1U case	120
YENİ			
iDS-7104HQHI-M1/T		4-ch 1080P Mini 1U H.265 AcuSense DVR Deep learning based human and vehicle targets classification of Motion Detection 2.0 Deep learning-based perimeter protection H.265 Pro+/H.265 Pro/H.265 video compression HDTV I/AHD/CVI/CVBS/IP video inputs Audio via coaxial cable Up to 6-ch IP camera inputs (up to 6 MP) Encoding ability up to 3K/5M Lite @ 12 fps	172
iDS-7104HQHI-M1/S		4 Kanal HD-TVI Kayıt Cihazı (5MP Lite) 2-ch perimeter protection , 4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch video&1-ch audio input, H.265/H.265+ compression,2-ch IP video input(up to 6-ch IP), 1 SATA interface Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, mini 1U case	157
DS-7204HGHI-M1		4 Kanal HD-TVI Kayıt Cihazı (1080P Lite) 4 Turbo HD/AHD/Analog interface input, 4-ch video&1-ch audio input, 1-ch IP video input, 1 SATA interface, HD1080P Lite: 25(P)/30(N) fps/ch, 260 1U case	120
YENİ			
DS-7204HGHI-M1/T		4 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio) Support HDTV I Two-way Audio technology, full-channel motion detection 2.0 ,4 Turbo HD/AHD/Analog interface input, 4-ch HDTV I coaxial video&audio input, 1-ch RCA audio input, 1-ch IP video input (up to 5-ch), 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, 260 1U case	128
YENİ			
iDS-7204HQHI-M1/T		4-ch 1080P 1U H.265 AcuSense DVR Deep learning based human and vehicle targets classification of Motion Detection 2.0 Deep learning-based perimeter protectio H.265 Pro+/H.265 Pro/H.265 video compression HDTV I/AHD/CVI/CVBS/IP video inputs Audio via coaxial cable Up to 6-ch IP camera inputs (up to 6 MP) Encoding ability up to 3K/5M Lite @ 12 fps	179
YENİ			
iDS-7204HQHI-M1/XT		4 Kanal HD-TVI Kayıt Cihazı (5MP Lite) TVI İki Yönlü Sesi Destekleyin DVR Support TVI Two-way Audio, 1-ch facial recognition or 2-ch advanced model perimeter protection , 4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface, Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, support CVBS output, standalone 1U case	201

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
YENİ			
iDS-7204HUHI-M1/T		4 Kanal HD-TVI Hibrit Kayıt Cihazı (8MP) Support TVI Two-way Audio,4-ch false alarm filter,4 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 4-ch HDTVl coaxial video&audio input, 1-ch RCA audio input, 4-ch IP video input(up to 8-ch IP), 1 SATA interface, H.265/H.265+ compression,Live view: 3K @20fps/ch,up to 8MP@8fps(CH1),3K @12fps/ch encoding capability, 260 1U case	266
8 KANAL TURBO HD DVR			
DS-7108HGHI-M1		8 Kanal HD-TVI Kayıt Cihazı (1080P Lite) 8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, 2-ch IP video input, HDMI & VGA Output, 1 SATA interface, HD1080P Lite: : 25(P)/30(N) fps/ch, mini 1U case	142
DS-7208HGHI-M1		8 Kanal HD-TVI Kayıt Cihazı (1080P Lite) 8 Turbo HD/AHD/Analog interface input, 8-ch video&1-ch audio input, 2-ch IP video input, HDMI & VGA Output, 1 SATA interface, HD1080P Lite: : 25)/(P30(N) fps/ch, 260 1U case	146
iDS-7108HQHI-M1/S		8 Kanal HD-TVI Hibrit Kayıt Cihazı (5MP Lite) 4-ch perimeter protection , 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 4-ch IP video input(up to 12-ch IP),1 SATA interface Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, mini 1U case	248
YENİ			
DS-7108HGHI-M1/T		8 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio) Support HDTVl Two-way Audio technology,full-channel motion detection 2.0 ,8 Turbo HD/AHD/Analog interface input, 8-ch HDTVl coaxial video&audio input,2-ch IP video input (up to 10-ch), 1-ch RCA audio input, HDMI & VGA Output, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, mini 1U case	146
YENİ			
DS-7208HGHI-M1/T		8 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio) Support HDTVl Two-way Audio technology,full-channel motion detection 2.0 ,8 Turbo HD/AHD/Analog interface input,8-ch HDTVl coaxial video&audio input, 1-ch RCA audio input, 2-ch IP video input (up to 10-ch), HDMI & VGA Output, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, 260 1U case	157
YENİ			
iDS-7108HQHI-M1/T		8-ch 1080P Mini 1U H.265 AcuSense DVR Deep learning based human and vehicle targets classification of Motion Detection 2.0 Deep learning-based perimeter protection H.265 Pro+/H.265 Pro/H.265 video compression HDTVl/AHD/CVI/CVBS/IP video inputs Audio via coaxial cable Up to 12-ch IP camera inputs (up to 6 MP) Encoding ability up to 3K/5M Lite @ 12 fps	263
YENİ			
iDS-7208HQHI-M1/T		8-ch 1080P 1U H.265 AcuSense DVR Deep learning based human and vehicle targets classification of Motion Detection 2.0 Deep learning-based perimeter protection H.265 Pro+/H.265 Pro/H.265 video compression HDTVl/AHD/CVI/CVBS/IP video inputs Audio via coaxial cable Up to 12-ch IP camera inputs (up to 6 MP) Encoding ability up to 3K/5M Lite @ 12 fps	270

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
iDS-7208HQHI-M1/XT		8 Kanal HD-TVI Kayıt Cihazı (5MP Lite) Support TVI Two-way Audio, 2-ch facial recognition or 4-ch advanced model perimeter protection , 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 8-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, support CVBS output, standalone 1U case	321
YENİ			
iDS-7208HUHI-M1/T		8 Kanal HD-TVI Hibrit Kayıt Cihazı (8MP) Support TVI Two-way Audio,4-ch false alarm filter, 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,8-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 8-ch IP video input(up to 16-ch IP), 1 SATA interface, H.265/H.265+ compression, Live view: 3K @20fps/ch,up to 8MP@8fps,3K @12fps/ch encoding capability, 4K UHD output, 260 1U case	471
16 KANAL TURBO HD DVR			
DS-7116HGHI-M1		16 Kanal HD-TVI Kayıt Cihazı (1080P lite) full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input, 16-ch HDTV coaxial video&audio input,2-ch IP video input (up to 18-ch), 1-ch RCA audio input, HDMI & VGA Output, 1 SATA interface, HD1080P Lite: 15fps/ch, mini 1U case	245
DS-7216HGHI-M1		16 Kanal HD-TVI Kayıt Cihazı (1080P Lite) full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input,16-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 2-ch IP video input (up to 18-ch), HDMI & VGA Output, 1 SATA interface, HD1080P Lite: 15fps/ch, 260 1U case	252
DS-7116HGHI-M1/T		16 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio) Support HDTV Two-way Audio technology,full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input, 16-ch HDTV coaxial video&audio input,2-ch IP video input (up to 18-ch), 1-ch RCA audio input, HDMI & VGA Output, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, mini 1U case	256
DS-7216HGHI-M1/T		16 Kanal HD-TVI Kayıt Cihazı (1080P Lite,Two-way Audio) Support HDTV Two-way Audio technology,full-channel motion detection 2.0 ,16 Turbo HD/AHD/Analog interface input,16-ch HDTV coaxial video&audio input, 1-ch RCA audio input, 2-ch IP video input (up to 18-ch), HDMI & VGA Output, 1 SATA interface, Live view: 1080P Lite: 25(P)/30(N) fps/ch, Up to 1080p Lite@15fps/ch encoding capability, 260 1U case	263
YENİ			
iDS-7116HQHI-M1/T		16-ch 1080P Mini 1U H.265 AcuSense DVR Deep learning based human and vehicle targets classification of Motion Detection 2.0 Deep learning-based perimeter protection H.265 Pro+/H.265 Pro/H.265 video compression HDTV/AHD/CVI/CVBS/IP video inputs Audio via coaxial cable Up to 24-ch IP camera inputs (up to 6 MP) Encoding ability up to 3K/5M Lite @ 12 fps	445
YENİ			
iDS-7216HQHI-M1/T		16-ch 1080P 1U H.265 AcuSense DVR Deep learning based human and vehicle targets classification of Motion Detection 2.0 Deep learning-based perimeter protection H.265 Pro+/H.265 Pro/H.265 video compression HDTV/AHD/CVI/CVBS/IP video inputs Audio via coaxial cable Up to 24-ch IP camera inputs (up to 6 MP) Encoding ability up to 3K/5M Lite @ 12 fps	489

ÜRÜN KODU (Model Number)	RESİM (Picture)	ÜRÜN AÇIKLAMASI / ÖZELLİK (Product Description)	Liste (MSRP)
YENİ IDS-7216HQHI-M1/XT		16 Kanal HD-TVI Kayıt Cihazı (5MP Lite) Support TVI Two-way Audio,4-ch facial recognition or 8-ch advanced model perimeter protection , 16 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 16-ch video&1-ch audio input, H.265/H.265+ compression, 1 SATA interface,Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, 4K UHD output, support CVBS output, standalone 1U case	569
YENİ IDS-7216HUHI-M1/T		16 Kanal HD-TVI Kayıt Cihazı (8MP) Support TVI Two-way Audio,4-ch false alarm filter, 8 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input,8-ch HDTV co axial video&audio input, 1-ch RCA audio input,16-ch IP video input(up to 32-ch IP), 1 SATA interface, H.265/H.265+ compression, Live view: 3K @20fps/ch,up to 8MP@8fps,3K @12fps/ch encoding capability, 4K UHD output,315 1U case	923
32 KANAL TURBO HD DVR			
DS-7232HGHI-M2		32 Kanal HD-TVI Kayıt Cihazı (1080P Lite) Deep learning based human and vehicle targets classification of Motion Detection 2.0; H.265 Pro+/H.265 Pro/H.265 video compression; HDTV/AHD/CVI/CVBS/IP video input; Audio via coaxial cable; Up to 18-ch IP camera inputs (up to 5 MP); Up to 1080p Lite@15 fps encoding capability; Max. 1200 m for 720p HDTV signal	694
YENİ IDS-7232HQHI-M2/XT		32 Kanal HD-TVI Kayıt Cihazı (5MP Lite) TVI İki Yönlü Sesi Destekleyen DVR Support TVI Two-way Audio,4-ch facial recognition or 8-ch advanced model perimeter protection , 32 Turbo HD/CVI / AHD / CVBS self-adaptive interfaces input, 32-ch video&1-ch audio input, 8-ch IP video input(up to 40-ch IP), H.265/H.265+ compression, 2 SATA interfaces,Live view: 3K Lite@20fps/ch,up to 3K Lite@12fps/ch encoding capability, 4K UHD output, support CVBS output, 380 1U case	1106

FİYAT LİSTESİ KULLANIM ŞARTLARI

- Bu liste fiyatı üretici tarafından önerilen fiyat listesidir.
- Ürünlerimiz 2 yıl ithalatçı firma garantisindedir.
- Vergi oranlarındaki değişiklikler fiyatlarımıza aynen yansıtılır.
- Belirtilen fiyatlara KDV oranı dahil değildir.
- Kayıt cihazlarında harddisk yoktur.Box Kameralara Lens dahil değildir.
- Fiyat listesinde belirtilen, fiyat bilgileri ,ürün kodları, ürün özellikleri, ürün açıklamaları değişiklik gösterebilir.
- Stoklar ve bulunmayan ürünlerin teslim süresi için Yetkili Distribütör firmadan bilgi alınması rica olunur.
- HIKVISION Dijital Teknoloji önceden haber vermeksizin listede yer alan fiyat koşullarını değiştirme haklarını gizli tutar.
- Oluşabilecek yazım, baskı ve dizgi hataları bağlayıcı değildir.

<http://www.hikvision.com/tr>